

CLAIMS

Claims pending at the time of the Restriction Requirement:

1-41.

Claims pending as a result of this response:

5 1-41.

Withdrawn claims in this response:

None.

Amended claims in this response:

None.

10 Cancelled claims in this response:

None.

This claim listing supplants all previous claim listings.

15 1. (Original) A label display system, comprising:

a deployable label base configured to display labels for a portable computing device; and

the deployable label base configured for movement between a first position and a second position, the labels being viewable in the first position and

20 at least some of the labels being concealed from view in the second position.

2. (Original) A label display system as recited in claim 1, wherein the deployable label base includes a first side to display one or more of the labels and at least a second side to display one or more of the labels.

25

3. (Original) A label display system as recited in claim 1, wherein the deployable label base is configured to display regulatory labels.

4. (Original) A label display system as recited in claim 1, wherein the
5 deployable label base is configured to display certification marking labels.

5. (Original) A label display system as recited in claim 1, wherein the deployable label base is further configured to rotate about a central longitudinal axis of the deployable label base.

10

6. (Original) A label display system as recited in claim 1, wherein the deployable label base is further configured to rotate about a central longitudinal axis of the deployable label base in the first position.

15

7. (Original) A label display system as recited in claim 1, wherein the deployable label base includes a first side to display one or more of the labels and at least a second side to display one or more of the labels, and wherein the deployable label base is further configured to rotate about a central longitudinal axis of the deployable label base, the one or more labels on the first side and the
20 one or more labels on the second side being viewable when the deployable label base is rotated.

8. (Original) A label display system as recited in claim 1, wherein the deployable label base is configured for slidable movement between the first position and the second position.

5 9. (Original) A label display system as recited in claim 1, wherein the deployable label base is flexible and further configured to be spooled in the second position.

10 10. (Original) A label display system as recited in claim 1, further comprising a theft deterrent configured to render the portable computing device inoperable if the deployable label base is removed from the portable computing device.

15 11. (Original) A label display system as recited in claim 1, wherein the deployable label base includes a security cable configured to secure the portable computing device.

20 12. (Original) A label display system as recited in claim 1, wherein the deployable label base encases a security cable configured to secure the portable computing device.

13. (Original) A label display system as recited in claim 1, wherein the deployable label base encases a security cable configured to secure the portable

computing device, and wherein the portable computing device is rendered inoperable if the security cable is removed from the portable computing device.

14. (Original) A label display system, comprising:

5 a deployable label base configured to display required labels for an electronic device; and

the deployable label base configured for movement between a first position and a second position, the labels being viewable in the first position and at least some of the labels being concealed from view in the second position.

10

15. (Original) A label display system as recited in claim 14, wherein the deployable label base includes a first side to display one or more of the required labels and at least a second side to display one or more of the required labels.

15

16. (Original) A label display system as recited in claim 14, wherein the deployable label base is configured to display regulatory labels.

17. (Original) A label display system as recited in claim 14, wherein
20 the deployable label base is configured to display certification marking labels.

18. (Original) A label display system as recited in claim 14, wherein the deployable label base is further configured to rotate about a central longitudinal axis of the deployable label base.

19. (Original) A label display system as recited in claim 14, wherein the deployable label base is further configured to rotate about a central longitudinal axis of the deployable label base in the first position.

5

20. (Original) A label display system as recited in claim 14, wherein the deployable label base is configured for slidable movement between the first position and the second position.

10 21. (Original) A label display system as recited in claim 14, wherein the deployable label base is flexible.

22. (Original) A label display system as recited in claim 14, wherein the deployable label base includes a security cable configured to secure the
15 electronic device.

23. (Original) A label display system as recited in claim 14, wherein the deployable label base encases a security cable configured to secure the
20 electronic device.

24. (Original) A label display system as recited in claim 14, wherein the deployable label base encases a security cable configured to secure the electronic device, and wherein the electronic device is rendered inoperable if the security cable is removed from the electronic device.

5

25. (Original) A method, comprising:

attaching labels for a portable computing device to a deployable label base;

the deployable label base being moveable between a first position and a second position, wherein the labels are viewable in the first position and at least some of the labels are concealed from view in the second position.

26. (Original) A method as recited in claim 25, wherein attaching includes attaching one or more of the labels to a first side of the deployable label base, and attaching one or more of the labels to at least a second side of the deployable label base.

27. (Original) A method as recited in claim 25, wherein attaching includes attaching regulatory labels.

20

28. (Original) A method as recited in claim 25, wherein attaching includes attaching certification marking labels.

29. (Original) A method as recited in claim 25, further comprising rotating the deployable label base about a central longitudinal axis of the deployable label base.

5 30. (Original) A method as recited in claim 25, further comprising rotating the deployable label base about a central longitudinal axis of the deployable label base, and wherein attaching includes attaching one or more of the labels to a first side of the deployable label base, and attaching one or more of the labels to at least a second side of the deployable label base.

10

31. (Original) A method as recited in claim 25, further comprising sliding the deployable label base between the first position and the second position.

15 32. (Original) A method as recited in claim 25, further comprising rendering the portable computing device inoperable if the deployable label base is removed from the portable computing device.

33. (Original) A method as recited in claim 25, further comprising
20 encasing a security cable with the deployable label base.

34. (Original) A method as recited in claim 25, further comprising encasing a security cable with the deployable label base, and rendering the

portable computing device inoperable if the security cable is removed from the portable computing device.

35. (Original) A method, comprising:
5 displaying required labels for an electronic device on a deployable label base;

the deployable label base being moveable between a first position and a second position, wherein the required labels are displayed in the first position and at least some of the required labels are concealed from display in the second
10 position.

36. (Original) A method as recited in claim 35, wherein displaying includes displaying one or more of the required labels on a first side of the deployable label base, and displaying one or more of the required labels on at
15 least a second side of the deployable label base.

37. (Original) A method as recited in claim 35, wherein displaying includes displaying regulatory labels.

20 38. (Original) A method as recited in claim 35, wherein displaying includes displaying certification marking labels.

39. (Original) A method as recited in claim 35, further comprising rendering the electronic device inoperable if the deployable label base is removed from the electronic device.

5 40. (Original) A method as recited in claim 35, further comprising encasing a security cable with the deployable label base.

 41. (Original) A method as recited in claim 35, further comprising encasing a security cable with the deployable label base, and rendering the
10 electronic device inoperable if the security cable is removed from the electronic device.